

2472·3150 Calcite Filter

Commercial Automatic



WATERWAYS

Quality ways with water

454.190

Product Description: Calcite is a food grade safe to drink pH adjustment mineral readily absorbed via flow of water through the material. Calcite filters are used to raise pH in acidic waters to a neutral level, typically pH 7.0 is optimum. Low pH waters are very corrosive and outside of safe water guidelines.

Specifications

| Туре | Automatic Calcite pH Correction Filter | |
|---------------|--|--|
| Description | Self standing pressure vessel (blue) with top mounted valve | |
| Media Tank | 24" (61cm) x 72" (183cm) wound fibreglass pressure vessel | |
| Media | 225kg of calcite | |
| Control Valve | Fleck 3150 5 stage regeneration Industrial valve Microprocessor backwash control | |
| Flow Rate | Continuous Peak | 300 litres per minute 325 litres per minute |
| Pressure | Maximum Minimum | 600 kpa (85 psi) 175 kpa (25 psi) |
| Pipe Sizes | Inlet/outlet Drain | 1 1/2" (40mm) 1" (25mm) |
| Voltage | 240 volts with 24 volts step down transformer | |
| | | |

Note: Product specifications are a guide only and can change without notice.

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160 Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com www.waterwaysproducts.com