



To us it's more than just water...



2162-2850 Mixed Bed Filter

Commercial Automatic



Est-1987

WATERWAYS

Quality ways with water

Product Description: Mixed bed filters are used for sediment removal over a wide range of flow rates. Due to a much larger surface area and the ability to be backwashed the dirt holding/handling capability of a mixed bed filter is far superior to cartridges. The beds can be made up of different filtering sands and filtration media.

Specifications

| | | |
|---------------|----------------------------------------------------------------------------------------|-----------------------|
| Type | Automatic Mixed Bed Filter | |
| Description | Self standing pressure vessel (blue) with top mounted valve | |
| Media Tank | 21" (51cm) x 62" (157cm) wound fibreglass pressure vessel | |
| Media | 160kg of mixed media Sand, anthracite and gravels | |
| Control Valve | Fleck 2850 3 stage regeneration Industrial valve Microprocessor backwash control | |
| Flow Rate | Continuous | 100 litres per minute |
| | Peak | 125 litres per minute |
| Pressure | Maximum | 600 kpa (85psi) |
| | Minimum | 175 kpa (25psi) |
| Pipe Sizes | Inlet/outlet | 1 1/2" (40mm) |
| | Drain | 1" (25mm) |
| Voltage | 240 volts with 24 volts step down transformer | |

Note: Product specifications are a guide only and can change without notice.



Est-1987 Australian Owned & Operated

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160
 PO Box 443 Lonsdale DC SA 5160
 Telephone 08 8186 0189 Facsimile 08 8382 7488
 Email: enquiries@waterwaysproducts.com
www.waterwaysproducts.com