



To us it's more than just water...

2472-3150 Mixed Bed Filter

Commercial Automatic



Est-1987

WATERWAYS

Quality ways with water

Product Description: Mixed bed filters are used for sediment removal over a wide range of flow rates. Due to a much larger surface area and the ability to be backwashed the dirt holding/handling capability of a mixed bed filter is far superior to cartridges. The beds can be made up of different filtering sands and filtration media.

Specifications

Type	Automatic Mixed Bed Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	24" (61cm) x 72" (183cm) wound fibreglass pressure vessel	
Media	275kg of mixed media Sand, anthracite and gravels	
Control Valve	Fleck 3150 5 stage regeneration Industrial valve Microprocessor backwash control	
Flow Rate	Continuous	300 litres per minute
	Peak	325 litres per minute
Pressure	Maximum	600 kpa (85psi)
	Minimum	175 kpa (25psi)
Pipe Sizes	Inlet/outlet	2" (50mm)
	Drain	1" (25mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.



Est-1987 Australian Owned & Operated

Waterways Products (Aust) Pty Ltd
 23 Aldershot Road, Lonsdale SA 5160
 PO Box 443 Lonsdale DC SA 5160
 Telephone 08 8186 0189 Facsimile 08 8382 7488
 Email: enquiries@waterwaysproducts.com
www.waterwaysproducts.com