

SA3 Mixed Bed Filter WARRAN Light Commercial Automatic





## **WATERWAYS**

Quality ways with water

**Product Description:** Mixed bed filters are used for sediment removal over a wide range of flow rates. Due to a much larger surface area and the ability to be backwashed the dirt holding/handling capability of a mixed bed filter is far superior to cartridges. The beds can be made up of different filtering sands and filtration media.

## **Specifications**

Туре	Automatic Mixed Bed Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	16" (41cm) x 65" (165cm) wound fibreglass pressure vessel	
Media	125kg of mixed media Sand, anthracite and gravels	
Control Valve	Fleck 5000 electronic valve, fast and rapid rinse, full adjustable function, 1-99 day backwash	
Flow Rate	Continuous Peak	50 litres per minute 60 litres per minute
Pressure	Maximum Minimum	600 kpa (85psi) 175 kpa (25psi)
Pipe Sizes	Inlet/outlet Drain	3/4" (20mm) 1/2" (12mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.

## Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160 Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com www.waterwaysproducts.com