

Product Description: Water softeners are typically used for removing calcium carbonate, manganese, iron and hardness from water sources and are regenerated by brine solutions. The treated water is soft and non scaling/staining. Commercial systems are available in single or twin (duplex) models and domestic units are available in cabinet style models.

Specifications

20re

Туре	Automatic Water Softener	
Description	Self standing pressure vessel (blue) with top mounted valve and separate brine tank (black)	
Capacity	165,000 litres at 100 mg/l hardness	
Media Tank	24" (61cm) x 72" (183cm) wound fibreglass pressure vessel	
Resin Capacity	250 litres of fine mesh cation resin	
Control Valve	Fleck 2850 3 stage regeneration Industrial Valve Volume (on demand) regeneration	
Brine Tank	24" (61cm) x 50" (127cm) with lid	
Flow Rate	Continuous Peak	160 litres per minute 180 litres per minute
Pressure	Maximum Minimum	600 kpa (85psi) 175 kpa (25psi)
Pipe Sizes	Inlet/outlet Drain	1 1/2" (40mm) 1" (25mm)
Salt Usage	24kg per regeneration	
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160 Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com www.waterwaysproducts.com

WATERWAYS

1.1 1.5 11 relief to same change your allowing